



Audible/Visual Alarm Light - YOdalex

YODALEX

AUDIBLE / VISUAL ALARM YL60 C N50 A EU
CE 0158 Ex II 2 GD



Ex d IIB+H2 T4 (Tamb -20°C to +60°C) Gb IP66
Ex d IIB+H2 T6 (Tamb -20°C to +40°C) Gb IP66
Ex tb IIIC T135°C (Tamb -20°C to +60°C) Db IP66
Ex tb IIIC T85°C (Tamb -20°C to +40°C) Db IP66

Baseefa 02 ATEX 0222 X

IECEX BAS 05.0087 X



INPUT = 230VAC

CURRENT = 100mA



HQ: R. STAHL, D-74638 Waldenburg

www.stahl-ex.com, Made in Germany

10002275097167



DATE of Manufacture: 16/20

WARNING

DO NOT OPEN WHEN AN EXPLOSIVE GAS OR DUST ATMOSPHERE IS PRESENT

CABLE ENTRY TEMPERATURE MAY EXCEED 70°C CABLING TO BE SUITABLE

POSSIBLE ELECTROSTATIC RISK: CLEAN ONLY WITH A DAMP CLOTH

CABLE ENTRY: (2 off) TAPPED M20x1.5 PITCH

(FOR ADAPTOR OR STOPPING PLUG)



kim@mars-eu.dk